



CLEMCO®

...the performance system.

TECHNICAL DATA SHEET

Note: For safe, efficient blasting, read and follow the owner's manual and seek training for everyone who will use this equipment.

Purpose

High-performance, versatile blast cleaning system removes contamination, corrosion, mill scale, and coatings from most surfaces. Produces a uniform surface texture, and creates a surface profile to increase bonding for coatings.

Model 2452 holds 6 cubic feet of abrasive providing 30 minutes of blasting at 100 psi with a No. 6 (3/8-inch) nozzle.

Requirements for Operation

These items are required but not included with this equipment:

- Clean, dry, compressed air of sufficient volume to maintain desired pressure at the nozzle. Refer to Air Consumption Chart in Blast Off 2 booklet (publication stock no. 09294).
- Minimum of 50 psi is needed to close the pop-up valve and pressurize the blast machine.
- OSHA-required remote control system that interrupts blasting if operator should lose control of the nozzle when blast machine is pressurized.
- NIOSH-approved, type CE, supplied-air respirator.
- Grade D breathing-air supply as defined by Compressed Gas Association Commodity Specification: G-7.1 (Refer to www.cganet.com).
- Abrasive blast media specifically manufactured for abrasive blasting and appropriate for your application.
- Appropriate blast suit, work boots, hearing and eye protection.

Description of Operation

The operator controls blasting from a remote control handle at the nozzle. Pressing the handle starts blasting; releasing it stops blasting. The blast machine contains abrasive and meters it into the compressed air stream.

Description

Yard-portable, heavy-duty, industrial, single-chamber blast machine rated at 150 psi working pressure. Model 2452 has 1-1/4 inch piping and holds 6 cubic feet of media (600 lbs expendable, mineral abrasive). This unit is equipped with FSV abrasive metering valve and remote controls. Complete system includes coupled hose, nozzle, supplied air respirator, and many accessories.

6 Cuft Classic Blast Machine Systems with 1-1/4" piping

*Model 2452 with
HP respirator and
accessories*




Advantages

- Yard portable, industrial-quality blast machines manufactured to ASME code.
- 1-1/4-inch piping allows up to 50 percent more air flow when compared with 1-inch piping.
- Industrial-quality valves, piping and fittings designed to maximize air flow and minimize energy required to operate the system.
- FSV abrasive metering valve maintains smooth, consistent, adjustable media flow.
- State-of-the-art NIOSH-approved respirator with DLX comfort-fit suspension.

Approvals and Certifications

Blast machine pressure vessel built to American Society of Mechanical Engineers (ASME) specifications for 150-psi working pressure. Vessel is hydrostatically tested and National Board-certified.

Remote control system complies with OSHA regulation 1910.244 (b).



**Model 2452: 6 cu ft Blast Machine, Classic
with 1-1/4" piping; 150 psi working pressure**

Item Description	Stock No.	Wt.
Without remotes:		
with FSV abrasive metering valve		
portable	01189	430
stationary	01190	430
With TLR 300 remotes:		
and FSV abrasive metering valve		
portable	01187	490
stationary	21073	490
and Manual Quantum metering valve		
portable	23769	480
and Sentinel abrasive metering valve		
with ACS (abrasive cut-off switch)		
portable	21068	500
stationary	21074	500
Systems		
2452-300-CA	00916	585
Includes: 1-1/4" piping, Blast machine 01187, Apollo 600 HP DLX (for use with compressed air) respirator with Clem-Cool Air Conditioner (CCAC), 50 ft. respirator hose, CPF 20 Breathing-air filter and Accessory Package		
2452-ACS-CA	23910	485
Includes: 1-1/4" piping, Blast machine 21062, Apollo 600 HP DLX respirator with Clem-Cool Air Conditioner (CCAC), 50 ft. respirator hose, CPF 20 Breathing-air filter and Accessory Package		
2452-300-AA	23895	585
Includes: 1-1/4" piping, Blast machine 01187, Apollo 600 LP DLX (for use with ambient air) respirator with Constant Flow Connector (CFC), 50 ft. respirator hose, and Accessory Package. CAP ambient air pump is an option.		

Item Description	Stock No.	Wt
Accessory Package		
1-1/2" Air filter w/ manual drain	22363	
50 ft. x 1-1/4" Supa hose w/ NHP-2 and CQPS-2	23481	42
Blast hose safety cable	15013	1.5
TXP-6 nozzle	23525	2
Blast machine screen, 24"	03100	
Poly all-weather cover	15143	
Leather gloves, 1 pair	02243	.5
Nylon ties, 8 ea.	02195	
CQGP-3 gaskets, pk of 10	08853	.5
NW-32 nozzle washers, pk of 10	91026	<.5
Abrasive trap screens, (6)	02012	<.5
Helmet outer lenses, pk of 25	04361	1
Options/Accessories		
Blast machine cover, 24"	02336	12
Metering valve, manual Quantum	22845	9
Carbon monoxide alarm, CMS-3 pkg	24612	4
Ambient Air Pumps		
CALIPSO, sgl operator	25908	73
CAP-4, 4 operators w/ frame	22530	175
CAP-4C, 4 operators w/ cart	22384	205
Blast suit, heavy cotton/leather		
S (08920), M (08921), L (08922), XL (08923)		
2XL (24201), 3XL (24202)		
Blast suit, seasonal cotton/nylon		
S (22913), M (22914), L (22915), XL (22916),		
2XL (22917), 3XL (25022), 4XL (24689)		
Operation Manuals		
Blast Machine without Remotes	06160	
Blast Machine with		
TLR300 Remotes	22501	
TLR300 with ACS	21260	
Sentinel Valve	20951	

ISO 9001:2008 certified. Clemco is committed to continuous product improvement. Specifications are subject to change without notice.