



SAFETY DATA SHEET

Part No. FM-10645CT-A (Liquid)

Revision Date: 9/25/2020

Supersedes Date: 9/16/2020

US Page: 1/9

Undercoating In A Can - Clear Wax

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1 - IDENTIFICATION

1.1 Product Identifier

Product Name : Undercoating In A Can - Clear Wax

Manufacturer Product Number : FM-10645CT-A

1.2 Other Means of Identification

Synonyms : None

Chemical Family : Mixture

1.3 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended Use : Corrosion Preventive Compound

Restrictions on Use : Uses other than those described above

1.4 Under Coating In A Can Supplier Details

	Manufacturer Details	Undercoating In A Can
Company Name	Daubert Chemical Company	Undercoating In A Can
Address	4700 S. Central Avenue Chicago, IL 60638 United States	454 South Main Street, Wilkes-Barre, PA 18703
Phone Number	1-708-496-7350	570-822-1151
Email	SDS@Daubert.com	

1.5 Emergency Phone Number

Emergency Number Chemtrec: (800) 424-9300

SECTION 2 - HAZARDS IDENTIFICATION

2.1 Classification of the Substance or Mixture

Classification of the chemical in accordance with paragraph (d) of §1910.1200:


GHS Classification:

Skin Corrosion/Irritation Category 2; Flammable Liquid Category 3;

Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

2.2 Label Elements

GHS Hazard Symbols



Signal Word

Warning

Hazard Statements

: Flammable liquid and vapor

: Causes skin irritation

: May cause drowsiness or dizziness



SAFETY DATA SHEET

Part No. FM-10645CT-A (Liquid)

Revision Date: 9/25/2020
Supersedes Date: 1/6/2020
US Page: 2/9

Undercoating In A Can - Rubberized

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Unclassified Hazards (HNOC)::

: None Identified

Precautionary Statements: Prevention:

: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

: Ground/bond container and receiving equipment.

: Use explosion-proof electrical/ventilating/lighting equipment.

: Use only non-sparking tools.

: Take precautionary measures against static discharge.

: Avoid breathing dust/fume/gas/mist/ vapors/spray.

: Wash thoroughly after handling.

: Use only outdoors or in a well-ventilated area.

: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

: If on skin: Wash with plenty of water

: If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

: If inhaled: Remove person to fresh air and keep comfortable for breathing.

: Call a poison center/doctor if you feel unwell.

: Specific treatment: see Section 4 on this SDS.

: If skin irritation occurs: Get medical advice/attention.

: Take off contaminated clothing and wash it before reuse.

: In case of fire: Use appropriate media to extinguish.

Storage:

: Store in a well-ventilated place. Keep container tightly closed.

: Store in a well-ventilated place. Keep cool.

: Store locked up.

Disposal:

: Dispose of contents/container to a suitable disposal site in accordance with local/national/international regulations.

2.3 Other Hazards Which Do Not Result In Classification

Hazards Not Otherwise Classified : No data available

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

3.1 Composition

Chemical name	Common name and synonyms	CAS #	%
Hydrotreated light distillate (Petroleum)	None	64742-47-8	60 - 80



SAFETY DATA SHEET

Part No. FM-10645CT-A (Liquid)

Revision Date: 9/25/2020
Supersedes Date: 1/6/2020
US Page: 3/9

Undercoating In A Can - Rubberized

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4 - FIRST-AID MEASURES

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Inhalation:	<i>If symptoms are experienced remove source of contamination or move victim to fresh air and obtain medical advice.</i>
Eye Contact:	<i>Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.</i>
Skin Contact:	<i>Wash with soap and water. Get medical attention if irritation develops or persists.</i>
Ingestion:	<i>Do not induce vomiting and seek medical attention immediately. Provide medical care provider with this SDS. If vomiting occurs, lean victim forward to reduce risk of aspiration into lungs.</i>
Most important symptoms/effects, acute and delayed:	<i>Causes skin irritation. May cause drowsiness or dizziness</i>
Indication of immediate medical attention and special treatment needed, if necessary:	<i>Consult a physician. Treat symptomatically.</i>

SECTION 5 - FIRE-FIGHTING MEASURES

5.1 Suitable (and Unsuitable) Extinguishing Media

Suitable Extinguishing Media *Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the fire.*

Unsuitable Extinguishing Media *Do not use water jet as an extinguisher, as this will spread the fire.*

5.2 Specific Hazards Arising from the Chemical or Mixture

Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death.

5.3 Special Protective Equipment and Precautions for Fire-Fighters:

*Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Use appropriate methods for the surrounding fire. **Hazardous combustion products:** Oxides of carbon, Calcium oxides, Sulfur oxides*



SAFETY DATA SHEET

Part No. FM-10645CT-A (Liquid)

Revision Date: 9/25/2020
Supersedes Date: 1/6/2020
US Page: 4/9

Undercoating In A Can - Rubberized

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

No health effects expected from the clean-up of this material, if contact can be avoided. Follow personal protective equipment recommendations found in Section VIII of this SDS

6.2 Methods and Materials for Containment and Cleaning up

Absorb or cover with dry earth, sand or other non-combustible material and transfer to appropriate waste containers. Use clean, non-sparking tools to collect absorbed material. Collect and discard in accordance with local, state and national regulations.

SECTION 7 - HANDLING AND STORAGE

7.1 Precautions for Safe Handling

Mildly irritating material. Avoid unnecessary exposure. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Ground and bond containers when transferring material. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. As with all chemicals, good industrial hygiene practices should be followed when handling this material.

7.2 Conditions for Safe Storage Including Any Incompatibilities

Safe storage conditions:

Store in a cool dry place. Isolate from incompatible materials. Keep away from heat, sparks, and flame. Keep container closed when not in use.

**Materials to Avoid/
Chemical**

Incompatibility:

Strong oxidizing agents



SAFETY DATA SHEET

Part No. FM-10645CT-A (Liquid)

Revision Date: 9/25/2020

Supersedes Date: 1/6/2020

US Page: 5/9

Undercoating In A Can - Rubberized

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical Component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Hydrotreated light distillate (Petroleum)		200 mg/m ³	No data available	No data available

8.1 Exposure Controls

Appropriate engineering controls:

- : Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.
- : Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits
- : Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910.

Individual protection measures, such as personal protective equipment:

Respiratory Protection: Proper ventilation (at a minimum) will be required when handling this product. Use respirators (NIOSH approved) only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator.

Respirator Type(s): NIOSH approved air purifying respirator with organic vapor cartridge.

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses.

Skin Protection: Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

Gloves: Nitrile

Other protective equipment: Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses.
Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

General hygiene conditions: Do not use pressure to empty container. Remove contaminated clothing and wash before reuse. Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Use with adequate ventilation "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Ground and bond containers when transferring material. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. As with all chemicals, good industrial hygiene practices should be followed when handling this material.



SAFETY DATA SHEET

Part No. FM-10645CT-A (Liquid)

Revision Date: 9/25/2020

Supersedes Date: 1/6/2020

US Page: 6/9

Undercoating In A Can - Rubberized

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Vapor Density	No Data Available	Evaporation Rate (nBac=1)	No Data Available
Viscosity	Typical 2500 cP	Partition Coefficient: n-octanol/water:	Not Available
Odor Threshold	No data available	Melting Point (°C):	Not Available
Physical State	Viscous Liquid	Freezing Point (°C):	Not Available
Appearance / Color	Off-white	Initial boiling point and boiling range (°C)	Not Available
Odor	Petroleum Type	Flash Point	>= 105 °F(41 °C)
Volatiles, % by weight:	61	Flammability (solid, gas):	No data available
VOC, Material, lb/gal	4.4	Relative density:	0.86
VOC, Material, grams/liter	524.6	Solubility(ies):	Negligible; 0-1%
VOC minus exempt solvents&water, g/l	524.6	Auto-ignition temperature (°C):	No data available
pH	No data available	Upper/lower flammability or explosive limits:	No data available

SECTION 10 - STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity: Not expected to be reactive

10.2 Chemical Stability

Chemical Stability: Stable under normal conditions.

10.3 Possibility of Hazardous Reactions

Hazardous Reactions: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to Avoid

Conditions to Avoid: Temperatures above flash point in combination with sparks, open flames, or other sources of ignition. Elevated temperatures. Contamination.

10.5 Incompatible Materials

Materials to Avoid: Strong oxidizing agents

10.6 Hazardous Decomposition Products

Thermal Decomposition: Under normal conditions of use & storage, decomposition and hazardous decomposition products are unlikely.

SECTION 11 - TOXICOLOGICAL INFORMATION

11.1 Numerical measures of toxicity (such as acute toxicity estimates):

Hydrotreated light distillate (Petroleum)

LC50 Inhalation (Rat) (4h) Rat > 20 mg/L

Is the hazardous chemical listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has it been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA?:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen.			



SAFETY DATA SHEET

Part No. FM-10645CT-A (Liquid)

Revision Date: 9/25/2020
Supersedes Date: 1/6/2020
US Page: 7/9

Undercoating In A Can - Rubberized

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- Routes Of Exposure** : Eye contact, Skin contact, Inhalation
- Symptoms related to the physical, chemical and toxicological characteristics:** : Causes skin irritation. . May cause drowsiness or dizziness
- Ingestion Toxicity:** : Harmful if swallowed. Estimated to be > 5.0 g/kg; practically non-toxic
- Skin Contact:** : Can cause minor skin irritation, defatting, and dermatitis.
- Inhalation Toxicity:** : No data available
- Eye Contact:** : Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.
- Sensitization:** : None known
- Mutagenicity:** : No data
- Reproductive and Developmental Toxicity:**
- Carcinogenicity:** : There are no carcinogenic ingredients present at or over 0.1%.
- STOT-single exposure:** : Classification has been based on toxicological information of the components in Section 3.
- STOT-repeated exposure:** : Based on available data, the classification criteria are not met.
- Aspiration hazard:** : Based on available data, the classification criteria are not met.

SECTION 12 - ECOLOGICAL INFORMATION

12.1 Ecological Toxicity Data:

No Data Available

CAS #	
Aquatic EC50 Crustacea	
Aquatic ERC50 Algae	
Aquatic LC50 Fish	

- Ecotoxicity (aquatic and terrestrial, where available):** No data available
- Persistence and degradability:** No data
- Bioaccumulative potential:** No data available
- Mobility in soil:** No data available
- Other adverse effects (such as hazardous to the ozone layer):** No data available

SECTION 13 - DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods

- Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging:** : Spent or discarded material is a hazardous waste.
: Dispose of by incineration following Federal, State, Local, or Provincial regulations.

- Waste codes / waste designations:** : D001



SAFETY DATA SHEET

Part No. FM-10645CT-A (Liquid)

Revision Date: 9/25/2020
Supersedes Date: 1/6/2020
US Page: 8/9

Undercoating In A Can - Rubberized

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14 - TRANSPORTATION INFORMATION

Domestic Ground in containers <= 119 GL *Corrosion preventive/Non-Regulated*

Domestic Ground in vessels < 119 gal. *UN1268, PETROLEUM DISTILLATES, N.O.S.,(Naphtha Solvent), Combustible liquid, PG III*

Shipping name for Export, Air (IATA) *UN1268, PETROLEUM DISTILLATES, N.O.S.,(Naphtha Solvent),3, PG III*

Shipping name for Export, Sea (IMDG) *UN1268, PETROLEUM DISTILLATES, N.O.S.,(Naphtha Solvent),3, PG III*

Marine Pollutant? *No*

SECTION 15 - REGULATORY INFORMATION

15.1 Status of formula components on selected national regulatory inventories:

LIST STATUS

TSCA All components in this product are on the TSCA Inventory or exempt.

Canadian DSL All chemical substances in this material are included on or exempted from listing on the Canadian DSL.

Chemical Name	CAS #	Regulation	Percent
Naphthalene	91-20-3	Prop. 65 - Cancer	TRACE
Cumene	98-82-8	Prop. 65 - Cancer	TRACE
Benzene	71-43-2	Prop. 65 - Cancer	TRACE
Ethylbenzene	100-41-4	Prop. 65 - Cancer	TRACE
Toluene	108-88-3	Prop. 65 - Developmental and/or Reproductive	<0.1
Benzene	71-43-2	Prop. 65 - Developmental and/or Reproductive	TRACE
Toluene	108-88-3	CERCLA	<0.1 RQ = 1000 lbs
Naphthalene	91-20-3	CERCLA	TRACE RQ = 100 lbs.
Cumene	98-82-8	CERCLA	TRACE RQ = 5000 lbs.
Benzene	71-43-2	CERCLA	TRACE RQ = 10 lbs.
Ethylbenzene	100-41-4	CERCLA	TRACE RQ = 1000 lbs.
Toluene	108-88-3	SARA 313	<0.1
Cumene	98-82-8	SARA 313	TRACE
Naphthalene	91-20-3	SARA 313	TRACE
Benzene	71-43-2	SARA 313	TRACE
Ethylbenzene	100-41-4	SARA 313	TRACE
No SARA 302 EHS-listed chemicals in this product.		SARA EHS	



SAFETY DATA SHEET

Part No. FM-10645CT-A (Liquid)

Revision Date: 9/25/2020
Supersedes Date: 1/6/2020
US Page: 9/9

Undercoating In A Can - Rubberized

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16 - OTHER INFORMATION

Indication of changes

Section	Changed item	Change
1	Created Safety Data Sheet - Revision 1	Added

Disclaimer of Liability

Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.